



Overall dimensions				Weight
	L	W	H	
4000	5600	170	150	Kg 2150
5000	6600	170	150	Kg 2330



TECHNICAL DATA

CUTTING LENGHT 4MT/5MT

Double head cutting off machine with raising blades for compound mitre cuts. With fixed unit on the left side and motorised movable unit on the right side. Pivoting range up to 140° outwards and up to 20° inwards with digital display. Pneumatic tilting range inwards 90°/45°. Equipped with double action vertical clamps, full protection of the saw blades, movable side support 2,5mts, pneumatic spray mist lubrication, complete with 2x TCT Saw Blades ø500mm. 2x Motors 3HP each.



STANDARD EQUIPMENT

EQUIPPED WITH ELECTRONIC POSITIONER ABLE TO:
 Manage single cuts
 Memorize 99 profile codes and their values
 Memorize cutting list already calculated via USB key
 Manage frame typologies (nr. 50)
 Software expanding capacity of cut on length
 Software reducing capacity of cut on length
 Metric ruler with reading index

OPTIONALS

Fixed side roller conveyor 2,5mts length
 Pneumatic central support
 Motorized belt conveyor 4mt useful cutting length
 Motorized belt conveyor 5mt useful cutting length
 Label printer
 Lubrication by micro drop with pure oil
 TCT Saw Blade D.500mm
 Emulsified cutting oil 20 lt

The specifications and illustrations in this catalogue are only a guide, Dynamic Machines Services Sdn Bhd therefore reserves the right to make any modifications it deems necessary for technical or commercial reasons.